

		DIST	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET TOTAL No. SHEETS
E = RFACE	CE					
	PLANS APPROVAL DATE					
	The State of California or its officers or agents shall not be responsible for the accuracy or completeness of scanned copies of this plan sheet. $S_{A_{1}C} \cap C_{AL}   FO^{R^{1}}$					
INER	Notes:		gistered Civil oper application	Engineer for the on of the compon	project is responsible fo ent design and any modifi	or the selection cations shown.
R = IGHT 	1. Cable Restrainer Pipes must be 2½" std galvanized pipe. The Pipes must be aligned to form a straight line the entire length of the restrainers and must be parallel to the Q girder. The pipes must not extend beyond the concrete faces and shall have smooth edges to prevent damage to restrainers. During construction pipe ends shall be capped to prevent debris intrusion.					
	<ol> <li>Anchorage surface must be perpendicular to the girder.</li> </ol>					
	<ol> <li>For View A-A, Section B-B and Anchorage details see: XS7-050-2, "Cable Restrainer Type 2 Details No.2 (New)" sheet.</li> </ol>					
	<ol> <li>For Cable Restrainer and Hardware details see: XS7-090, "Cable Restrainer Hardware Details" sheet.</li> </ol>					
	5. Reinforcement not shown.					
	1 Plac	e pipes	2" clear	from ma	in hinge reinfo	prcement.
		REINF SEI ON B-B -			CONCRETE ANCHORAGI	BAR = BAR =
					I	Ż
	_SUPPORT (Standard Anc					
NO.						
AILE						
_	CABLE RES	STRAIN	IER T	PE 2 D	ETAILS No	.1 (NEW)
NTRACT	NO.:	DISREGARD EARLIER RE	PRINTS BEARI VISION DATES		REVISION DATES	SHEET OF