

# Appendix D Example 30 – Short Poured-In-Place Concrete Piles

Refer to *Falsework Manual*, Section 5-6, *Short Poured-In-Place Concrete Piles* and the sample calculations in Appendix D Example 29 – *Short Poured-In-Place Concrete Piles*. This example demonstrates how to perform a complete analysis for a short poured-in-place concrete pile.

## Given Information

A contractor proposes to use an 18-inch diameter poured in place concrete pile as an anchorage for his falsework cable bracing. Prior to being used for bracing the falsework this pile will be used as an anchorage for the column reinforcing cage and form.

This anchor pile will be subjected to three short term loads in the same direction.

Soil (cohesionless):

Internal Friction  $\phi = 35^\circ$

Unit weight  $\gamma_s = 110$  pcf

Concrete:

Unit weight  $\gamma_c = 145$  pcf

Compressive strength  $f'_c = 3250$  psi

Bar Reinforcing Steel:

2-#5 Grade 60 bars, full length each side of centerline

Pile Dimensions:

$a = 2$  in.

$b = 6 \frac{1}{4}$  in

$d = 18$  in = 1.5 ft


$e = 1.2$  ft

$\theta = 35^\circ$

$L = 12$  ft (lower 2 ft submerged)

Design load:

$P = 8000$  lbs



**Figure D-30-1. Laterally Loaded Reinforced Concrete Pile**

## Determine the Adequacy of the Pile

### Check for adequate reinforcement clearance

Find distance from center of pile to center of bar (use geometry) and bar radius

$$9 \text{ in} - \left\{ \sqrt{(6.25)^2 + (2)^2} + \frac{0.625}{2} \right\} = 2.13 \text{ in} > 2 \text{ in minimum clearance} \quad \underline{\text{OK}}$$

### Calculate load components

$$H_{\text{DESIGN}} = \text{Design} \cos 35^\circ = (8000) (\cos (35^\circ)) = 6553 \text{ lbs}$$

$$V_{\text{DESIGN}} = \text{Design} \sin 35^\circ = (8000) (\sin (35^\circ)) = 4589 \text{ lbs}$$

### Calculate Factor of Safety

$$\begin{aligned} \text{FS} &= 2.0 + (x-1) (0.25) = 2.0 + (3-1) (0.25) && (5-6.03-1) \\ &= 2.5 \text{ for lateral soil loading} \end{aligned}$$

### Check Uplift Capacity

$$S = \beta \sigma_z$$

where:

$$z = 12 \text{ ft} \quad (Z_{\text{dry}} = 10 \text{ ft}; Z_{\text{wet}} = 2 \text{ ft})$$

$$\sigma_z = 10(110) + 2(110 - 62.4) = 1195 \text{ psf}$$

$$\beta = 1.5 - 0.315 z^{1/2} = 1.5 - 0.315(12)^{1/2} = 0.41 > 0.25 \quad \underline{\text{OK}}$$

$$S = 0.41 (1,195) = 490 \text{ psf} \quad 4,000 \text{ psf} \quad \text{OK}$$

$$\text{Net pile shearing resistance } R_s = \pi dzS = \pi(1.5)(12)(490) = 27,709 \text{ lbs}$$

$$\text{Pile weight } W = \pi \left(\frac{d}{2}\right)^2 L_p \gamma_c = \pi \left(\frac{1.5}{2}\right)^2 (12 + 1.2)(145) = 3382 \text{ lbs}$$

$$\text{Ultimate load capacity } R = 27,709 + 3382 = 31,091 \text{ lbs}$$

$$\text{Working load } V = \frac{31,091}{2.5} = 12,436 \text{ lbs} > 4,589 \text{ lbs} \quad \underline{\text{OK}}$$

**Check lateral capacity**

$$4d = (4)(1.5) = 6.0 \leq 12 \text{ ft (Meets minimum embedment length requirements)}$$

$$K_p = \tan^2 \left( 45^\circ + \frac{\phi}{2} \right) = \tan^2 \left( 45^\circ + \frac{35^\circ}{2} \right) = 3.69$$

$$L/d = 12/1.5 = 8.0 \leq 20 \text{ (meets short pile criteria)}$$

$$e/d = 1.2/1.5 = 0.8$$

From Figure 5-23, 
$$\frac{H_{ULT}}{K_p \gamma_s d^3} \approx 16$$

Find effective unit weight of soil by using weighted average to account for variable soil layers:

$$\gamma_2 = \frac{(10)(110) + (2)(110 - 62.4)}{12} = 99.6 \text{ pcf}$$

$$H_{ULT} = 16 \times K_p \gamma_s d^3 = 16 \times (3.69)(99.6)(1.5)^3 = 19,846 \text{ lbs}$$

Working Load Value for  $H_{ULT} = \frac{19,846}{2.5} = 7938 \text{ lbs} > 6533 \text{ lbs}$  **OK**

$$(f_g)^2 = \frac{H_{ULT}}{1.5 \gamma_s d K_p} \quad (5-6.03A-1)$$

$$f_g = \left( \frac{H_{ULT}}{1.5 \gamma_s d K_p} \right)^{\frac{1}{2}} = \left( \frac{19,846}{1.5 (99.6)(1.5)(3.69)} \right)^{\frac{1}{2}} = 4.90 \text{ ft}$$

$$\begin{aligned} M_{ULT} &= H_{ULT} \left( e + \frac{2f_g}{3} \right) \\ &= (19,846) \left( 1.2 + \frac{(2)(4.90)}{3} \right) = 88,645 \text{ ft-lb} \end{aligned}$$

Working Load Value for  $M_{ULT} = \frac{88,645}{2.5} = 35,458 \text{ ft-lb}$

**Pile Adequacy**

Pile capacity is to be based on design loads. The lateral force  $H_{DESIGN}$  may be substituted for  $H_{ULT}$  and  $M_{DESIGN}$  for  $M_{ULT}$  in the critical soil equations.

$$V_{\text{DESIGN}} = 4,589 \text{ lbs}$$

$$H_{\text{DESIGN}} = 6,553 \text{ lbs}$$

$$(f_g)^2 = \frac{H_{\text{ULT}}}{1.5 \gamma_s d K_p} \quad (5-6.03A-1)$$

$$f_g = \left( \frac{H_{\text{ULT}}}{1.5 \gamma_s d K_p} \right)^{\frac{1}{2}} = \left( \frac{6553}{1.5 (99.6)(1.5)(3.69)} \right)^{\frac{1}{2}} = 2.82 \text{ ft}$$

$$M_{\text{DESIGN}} = M_{\text{ULT}} = H_{\text{ULT}} \left( e + \frac{2f_g}{3} \right) \quad (5-6.03A-2)$$

$$M_{\text{DESIGN}} = 6553 \left( 1.2 + \frac{(2)(2.82)}{3} \right) = 20,183 \text{ ft-lb}$$

$$\text{Depth to plane of zero shear of pile} \approx \frac{M_{\text{DESIGN}}}{H_{\text{DESIGN}}} \approx \frac{20,183}{6,553} = 3.08 \text{ ft}$$

### Concrete Stress

$$\text{Pile weight} = \pi \left( \frac{d}{2} \right)^2 (3.08 + e) \gamma_c = \pi \left( \frac{1.5}{2} \right)^2 (3.08 + 1.2)(145) = 1096 \text{ lbs}$$

$$V' = 4589 - 1096 = 3493 \text{ lbs}$$

$$I_g = \frac{\pi d^4}{64} = \frac{\pi (18)^4}{64} = 5153 \text{ in}^4$$

$$A_g = \frac{\pi d^2}{4} = \frac{\pi (18)^2}{4} = 254.5 \text{ in}^2$$

$$f_c = \frac{M d}{2 I_g} - \frac{V'}{A_g} \leq \frac{f'_c}{2} \quad (5-6.04-1)$$

$$f_c = \frac{(20,183)(12)(1.5)(12)}{(2)(5153)} - \frac{3493}{254.5} = 409 \text{ psi} < 1625 \text{ psi} = \frac{f'_c}{2} \quad \text{OK}$$

$$V_u = 2\sqrt{f'_c} = 2\sqrt{3250} = 114 \text{ psi}$$

$$V_u = \frac{v}{0.5bd} \approx \frac{v}{0.5A} \approx \frac{6,553}{(0.5)(254.5)} \approx 51 \text{ psi}$$

51 psi < 114 psi allowable **OK**

### Bar Reinforcing Stress

$$A_s = 0.31 \text{ in}^2 \quad d_{\text{bar}} = 0.625 \text{ in}$$

$$d_s = 2b = (2)(6.25) = 12.50 \text{ in}$$

$$\Sigma A_s = 4(0.31 \text{ in}^2) = 1.24 \text{ in}^2$$

$$f_s = \frac{M}{A_s d_s} + \frac{V'}{\Sigma A_s} = \frac{(20,183)(12)}{(2 \times 0.31)(12.50)} + \frac{3493}{1.24} = 34,068 \text{ psi}$$

$$F_s \leq 0.70 F_y = 0.7 (60,000) = 42,000 \text{ psi} \quad (5-6.05-4)$$

34,068 psi < 42,000 psi allowable **OK**

This pile is capable of resisting the applied loads. The pile is satisfactory for use as designed by the contractor.