



California Manual on Uniform Traffic Control Devices

FHWA's MUTCD 2009 Edition as amended for use in California

California MUTCD Training

8:00 am – 5:00 PM

Thursday

April 26, 2012

Caltrans District 4 Office

Main Auditorium

111 Grand Ave.,

Oakland, CA 94612

Instructors:

Roberta McLaughlin, Don Howe & Johnny Bhullar, Caltrans HQ Traffic Operations

To register, please e-mail :

Bao.Chan@dot.ca.gov

2012 Edition

PLEASE NOTE:

- See attached agenda and detailed list of topics that will be covered.
- Class is free and open to Caltrans, local agencies & private practitioners.
- Registration is mandatory to ensure seats are available for everyone.



California MUTCD 2012 Training (April 26, 2012 – Oakland) Topics



AGENDA

8:00 – 9:00 AM Overview (Introduction & Part 1 – General)

9:00 – 9:30 AM Part 2 (Signs)

9:30 – 9:50 AM BREAK

9:50 – 11:30 AM Part 2 (Signs) Continued

11:30 – 12:30 PM LUNCH

12:30 – 1:00 PM Part 2 (Signs) Continued

1:00 – 2:10 PM Part 3 (Markings)

2:10 – 2:30 PM BREAK

2:30 – 3:40 PM Part 6 (Temporary Traffic Control)

3:40 – 4:00 PM BREAK

4:00 – 4:30 PM Part 7 (Traffic Control for School Areas)

4:30 – 4:45 PM Part 9 (Traffic Control for Bicycle Facilities)

4:45 – 5:00 PM Q & A

California MUTCD 2012 Training (April 26, 2012 – Oakland) Topics



List of overview topics covered in this training

Introduction

- Federal and state legal requirements and references.
- Applicability on public roadways, local agencies and private property.
- Relationship with other documents, such as National MUTCD, Caltrans Standard Plans, Standard Specifications and Standard Special Provisions.
- Meaning, format, interpretation and applicability of Standard, Guidance, Option, and Support text headings.
- Layout and description of manual parts, chapters, sections, figures and tables.
- Font, format, nomenclature for making distinction between National MUTCD and California added/modified contents.
- Compliance of new highway or bikeway construction or reconstruction projects.
- Compliance and flexibility allowed on projects in various phases from design through construction, for existing devices on roadway that have become non-compliant and for existing inventory of non-compliant devices.
- Compliance for devices identified with specific target compliance dates.

Part 1 - General

- Sections 1A.03 thru 1A.06: Responsibility for design, placement, operation, maintenance, and uniformity of traffic control devices.
- Section 1A.07: California MUTCD in “substantial conformance” with National MUTCD.
- Section 1A.07: Legal requirement providing Caltrans authority to issue California MUTCD after consultation with local agencies and public hearings.
- Section 1A.07: California MUTCD applicability to privately owned and maintained roads or commercial establishments.
- Section 1A.08: Authority for placement of traffic control devices.
- Section 1A.09: Engineering Study and Engineering Judgment.
- Section 1A.12: Color code.

Part 2 - Signs

2A – General

- Section 2A.06: Use of pictographs
- Section 2A.12: Symbol used for a given category of signs not be used for a different category of signs.
- Section 2A.13: Word messages – use/non-use of different characters, symbols, fractions, upper-case, lower-case and mixed-case letters.

2B – Regulatory Signs

- Section 2B.03: Size of Regulatory Signs.
- Section 2B.11: Yield Here To Pedestrians Signs.
- Section 2B.12: In-Street and Overhead Pedestrian Crossing Signs.
- Section 2B.13: Speed Limit changes and AB529 related changes.
- Section 2B.36: DO NOT DRIVE ON SHOULDER Sign and DO NOT PASS ON SHOULDER Sign
- Section 2B.43 thru 2B.45: Roundabout Directional Arrow Sign and Circular Plaque.
- Section 2B.52: Traffic Signal Pedestrian and Bicycle Actuation Signs.
- Section 2B.53: Traffic Signal Signs.

California MUTCD 2012 Training (April 26, 2012 – Oakland) Topics



2C – Warning Signs

- Section 2C.04: Minimum size of diamond-shaped warning sign on multi-lane roads, when used on the left-hand side or facing traffic.
- Section 2C.06 thru 2C.15: Horizontal Alignment Warning Signs and Table 2C-5 indicating that a horizontal alignment sign is required, recommended, or allowed based on speed differentials.
- Section 2C.08: Advisory Speed Plaque and change in ball-bank criteria to 12, 14 and 16.
- Section 2C.09: Enhanced use of Chevron Alignment Signs and spacing per new Table 2C-6. Prohibited use of chevron signs.
- Section 2C.10: Combination Horizontal Alignment/Advisory Exit and Ramp Speed Signs.
- Section 2C.12: One-Direction Large Arrow Sign not to be used at Roundabouts.
- Section 2C.15: Combination Horizontal Alignment/Advisory Exit and Ramp Speed Signs.
- Section 2C.24: Freeway or Expressway Ends Signs
- Section 2C.33: Warning Signs and Plaques for Motorcyclists
- Section 2C.34: NO CENTER LINE Sign
- Section 2C.35: Weather Condition Signs
- Section 2C.38: Reduced Speed Limit Ahead Signs
- Section 2C.40: Merge (W4-1) sign and Entering Roadway Merge (W4-5) sign with a NO MERGE AREA (W4-5P) supplemental plaque
- Section 2C.49: combined Bicycle/Pedestrian (W11-15) sign TRAIL X-ING (W11-15P) supplemental plaque
- Section 2C.52: NEW TRAFFIC PATTERN AHEAD Sign

2D & 2E – Guide Signs on Conventional Roads, Freeways and Expressways.

- Section 2D.43: Street Name signs.
- Section 2D.45: Guide signs on multi-lane conventional roads approaching an interchange, to identify which direction of turn is to be made and/or which specific lane to use.
- Section 2D.50: Community Wayfinding Signs.
- Section 2D.101(CA): Mile Post Markers – *who determines how these are placed.*
- Section 2E.19: Arrows for Interchange Guide Signs.
- Section 2E.22: Design of Freeway and Expressway Diagrammatic Guide Signs for Option Lanes
- Section 2E.35: Use of pictographs on supplemental guide signs.
- Section 2E.36: LAST EXIT BEFORE TOLL (W16-16P) plaque.

2F – Toll Road Signs.

- Entire Chapter is new.

2G – Preferential and Managed Lane Signs.

- Entire Chapter is new. Former HOV sections have been extensively re-written.
- Entire Chapter is new.

2M – Recreational and Cultural Interest Area Signs.

- Section 2M.07: Use of Prohibitive Circle and Diagonal Slash for Non-Road Applications.

Part 3 - Markings

3A – General

- Section 3A.05: Purple markings supplementing lane line or edge line markings for toll plaza lanes restricted to use by vehicles with registered electronic toll collection accounts.

3B – Pavement and Curb Markings

- Section 3B.01: Single solid yellow line not to be used as a center line marking on a two-way roadway.

California MUTCD 2012 Training (April 26, 2012 – Oakland) Topics



- Section 3B.02: Table 3B-1 is for operational use in marking no-passing zones, values are less than that suggested for geometric design by the AASHTO Policy on Geometric Design of Streets and Highways.
- Section 3B.04: Lane line markings for deceleration or acceleration lanes, through lane that becomes a mandatory exit or turn lane, auxiliary lane 2 miles or less in length between an entrance ramp and an exit ramp or auxiliary lane 1 mile or less in length between two adjacent intersections.
- Section 3B.04: Lane line markings in advance of lane drops at exit ramps, in advance of freeway route splits with dedicated lanes, to separate a through lane that continues beyond an interchange from an adjacent auxiliary lane between an entrance ramp and an exit ramp, as a lane drop marking in advance of lane drops at intersections or to separate a through lane that continues beyond an intersection from an adjacent auxiliary lane between two intersections.
- Section 3B.18: Use of engineering study before installing a marked crosswalk.
- Section 3B.18: Detectable warning surfaces to mark boundaries between pedestrian and vehicular ways.

3C – Roundabout Markings.

- Entire Chapter is new.

3D – Markings for Preferential Lanes.

- Entire Chapter is new. Former HOV sections have been extensively re-written.

3E – Markings for Toll Plazas.

- Entire Chapter is new.

3F – Delineators.

- Section 3F.03: Use of delineators on guardrail or other longitudinal barriers.

3G – Colored Pavements.

- Section 3G.01: When colored pavement is or is not a traffic control device.

3J – Rumble Strip Markings.

- Entire Chapter is new.

Part 6 – Temporary Traffic Control

6A – General

- Section 6A.01: Use of ITS in work zones for operational improvements.

6C – Temporary Traffic Control Elements

- Section 6C.04: Table 6C-1 sign spacing distances are approximate, should be adjusted for field conditions, to provide additional reaction time or in order to place a sign immediately downstream of an intersection.
- Section 6C.05: Use of more dominant devices in mobile operations.
- Section 6C.10: Traffic control can be self-regulating on low-volume roadways if road users from both directions are able to see the traffic through and beyond the worksite.

6D – General

- Section 6D.01: If establishing or maintaining an alternate pedestrian route is not feasible, an alternate means for pedestrians, such as adding free bus service or assigning someone the responsibility to assist pedestrians with disabilities, may be used.

6E – Flagger Control

- Section 6E.03: The bottom of the STOP/SLOW sign portion of the paddle should be a minimum of 6 feet above the pavement when mounted on a rigid staff.
- Section 6E.03: Use of traffic baton made of a flashlight with a red glow cone when flagging in an emergency situation at night in a non-illuminated flagger station.
- Section 6E.04 thru 6E.06: Automated Flagger Assistance Devices.

California MUTCD 2012 Training (April 26, 2012 – Oakland) Topics



- Section 6E.07: Flaggers prohibited to use of hand movements alone without a paddle, flag, or AFAD to control road users.
- Section 6E.08: Flaggers should identify an escape route.

6F – Traffic Control Zone Devices

- Section 6F.01: MUTCD crashworthiness provisions apply to all public roadways in California.
- Section 6F.02: The minimum sizes column shall only be used where the 85th-percentile speed or posted speed limit is less than 35 mph.
- Section 6F.03: Signs mounted on portable sign supports not meet the minimum 5 and 7 feet mounting heights provided should not be used for a duration of more than 3 days.
- Section 6F.12: Work Zone and Higher Fines Signs and Plaques.
- Section 6F.29: EXIT ONLY Sign (E5-3).
- Section 6F.30: NEW TRAFFIC PATTERN AHEAD Sign (W23-2).
- Section 6F.46: STEEL PLATE AHEAD Sign (W8-24).
- Section 6F.48: Reverse Curve Signs (W1-4 Series).
- Section 6F.54: Motorcycle Plaque (W8-15P).
- Section 6F.61: Use of alternating diamond mode.
- Section 6F.63 & 6F.83: Use of a series of sequential flashing warning lights to increase driver detection and recognition of the merging taper.
- Section 6F.65: Distinction between non-cylindrical tubular marker or channelizer (CA) and portable delimiters.
- Section 6F.72: Temporary Lane Separators.
- Section 6F.79: Use of retroreflective or internally illuminated raised pavement markers.
- Section 6F.79: Color and pattern of the raised pavement markers shall simulate the color and pattern of the markings they substitute.
- Section 6F.84: Temporary traffic control signals shall not be located within 200 feet of a grade crossing unless it is provided with preemption, or unless a uniformed officer or flagger is provided at the crossing to prevent vehicles from stopping within the crossing.

6G – Type of Temporary Traffic Control Zone Activities

- Section 6G.01: TTC plan is needed for any planned special event that will have an impact on traffic.
- Section 6G.12: If operating speeds are 40 mph or less and space approaching the work area does not permit moving traffic over one lane at a time, a single continuous taper can be used.

6H – Typical Applications

- TA 101(CA): (New) Shoulder Closure on Urban (Low Speed) Locations to Accommodate Bicyclists.
- TA 102(CA): (New) Lane Closure on Freeway, Expressway, Rural and Urban (High Speed) Locations to Accommodate Bicyclists.
- TA 103(CA): (New) Detour for Bike Lane on Roads with Closure of One Travel Direction.
- TA 104(CA): (New) Right Lane and Bike Lane Closure on Far Side of Intersection.
- TA 105(CA): (New) Lane Shift on Road with Low Traffic Volumes.

6I – Traffic Control Through Traffic Incident Management Areas

- Section 6I.02 & 6I.03: Use of light sticks.

Part 7 – Traffic Control for School Areas

7B – Signs

- Section 7B.07: FYG color background required on school warning signs.
- Section 7B.08, 7B.09, 7B.11, 7B.12 & 7B.15: Revised School Assembles A(CA) thru E(CA).
- Section 7B.12: In-Street Schoolchildren Crossing (Yield) sign.

California MUTCD 2012 Training (April 26, 2012 – Oakland) Topics



- Section 7B.13: School Bus Stop Ahead Sign (S3-1).
- Section 7B.14: SCHOOL BUS TURN AHEAD Sign (S3-2).
- Section 7B.15: END SCHOOL SPEED LIMIT (S5-3) sign.
- Section 7B.15: EXTENDED 25 MPH AND/OR REDUCED SPEEDS IN SCHOOL ZONES.
- Section 7B.16: Use of Reduced School Speed Limit Ahead (S4-5, S4-5a) sign where the speed limit is being reduced by more than 10 mph.

7C – Markings

- Section 7C.02: Warning signs should be installed for all marked school crosswalks at non-intersection locations.

Part 9 – Traffic Control for Bicycle Facilities

9B – Signs

- Section 9B.02: Minimum plaque sizes.
- Section 9B.06: Bicycles May Use Full Lane Sign (R4-11).
- Section 9B.18: Combined Bicycle/Pedestrian (W11-15) sign and TRAIL X-ING (W11-15P) supplemental plaque are new.
- Section 9B.21: Bicycle Route (M1-8a) sign is new.
- Section 9B.22: Bicycle Route Sign Auxiliary Plaques.
- Section 9B.25: Mode-Specific Guide Signs for Shared-Use Paths (D11-1a, D11-2, D11-3, D11-4).

9C – Markings

- Section 9C.07: Shared Lane Marking.