CODE G78



NOTE:

On overhead mounted signs, with lighting and catwalks, bottom border shall be omitted.

NOTE:
For destinations in line 2 use 6 & 4½ (G78-1), 8 & 6 (G78-2), or 10.67 & 8 (G78-3).

ALL DIMENSIONS ARE IN INCHES

G78 SUFFIX	SIZE	BORDER WIDTH	MARGIN WIDTH	LETTER SIZE, SERIES & STROKE WIDTH					COR RAD.
				LINE 1	LINE 2	LINE 3	LINE 4	LINE 5	
-1.2	Var x42	1	-	8 NUM	6 CAP				6
-2.3	Var x54	1¼	-	10NUM	8 CAP				6
-3.2	Var x66	1½	-	10 NUM	10 CAP				6

G78 SUFFIX	SIZE	DIMENSIONS											
		A	B	C	D	E	F	G	H	I	J	K	L
-1.2	Var x42	6	6										
-2.3	Var x54	8	7										
-3.2	Var x66	10	10½										

Green BACKGROUND WITH White BORDER & SYMBOL

Reflective message & border

Refer to standard arrow sheet & post spacing table

APPROVED

TRAFFIC ENGINEER — DATE 11/15/71 — REVISION 7/25/72 — 7/15/73

HT-69 REV 12 30 69